

## SMWC50 SERIES

## 50W Single Constant Current Output LED Driver



- Wide Input Voltage 90 to 305VAC, 47 to 63Hz
- Over Voltage / Short Circuit / Over Temperature Protection
- High Efficiency (up to 88%), Active Power Factor Correction (PFC)
- IP67 Waterproof Rating, Fully isolated
- Comply to worldwide safety regulations for lighting
- Cooling by free air convection
- Suitable for LED lighting & moving sign applications, for dry / damp / wet locations

5 Year Warranty


Approvals: IP67  

### SPECIFICATION

Part Number		SMWC050-0350SS/D	SMWC050-0700SS/D	SMWC050-1050SS/D	SMWC050-1400SS/D
OUTPUT	DC VOLTAGE	86-143V	43 -71V	29-48V	21-36V
	CONSTANT CURRENT REGION Note.4	350mA	700mA	1050mA	1400mA
	RATED POWER	50W			
	RIPPLE & NOISE(max.) Note.2	6.8V	4.8V	3.8V	3.7V
	CURRENT TOLERANCE Note.3	±5.0%			
	LINE REGULATION	±2.0%			
	LOAD REGULATION	±3.0%			
	SETUP, RISE TIME(Typ.) Note.7	1500ms/50ms 115VAC at full load		500ms/50ms 230VAC	
INPUT	VOLTAGE RANGE Note.5	90 ~305VAC			
	FREQUENCY RANGE	47 ~ 63Hz			
	POWER FACTOR(Typ.)	0.99@115VAC 60HZ	0.99@115VAC 60HZ	0.99@115VAC 60HZ	0.99@115VAC 60HZ
	EFFICIENCY(Typ.)	90%	89.5%	89%	88.5%
	AC CURRENT(Typ.)	0.6A/115VAC		0.3A/230VAC	
	INRUSH CURRENT(Typ.)	COLD START 48A ( Twidth=270us measured at 50% Ipeak ) at 230VAC			
	LEAKAGE CURRENT	<0.75mA/265VAC			
PROTECTION	OVER CURRENT Note.4	95 ~ 108% Protection type: Constant current limiting, recovers automatically after fault condition is removed			
	SHORT CURRENT	Hiccup mode, recovers automatically after fault condition is removed			
	OVER VOLTAGE	160V	90V	63V	48V
		Protection type: Hiccup mode, recovers automatically after fault condition is removed			
	OVER TEMP.	Hiccup mode, recovers automatically after fault condition is removed			
ENVIRONMENT	WORKING TEMP.	-35 ~ +70℃ (Refer to "Derating Curve")			
	WORKING HUMIDITY	10 ~ 100% RH non-condensing			
	STORAGE TEMP., HUMIDITY	-40 ~ +85℃, 5 ~ 100% RH			
	TEMP. COEFFICIENT	±0.03%/℃ (0~50℃)			
	VIBRATION	10 ~ 500Hz, 5G 12min./1cycle, period for 72min. each along X, Y, Z axes			
SAFETY & EMC	SATETY STANDARDS Note.6	UL8750, UL935, UL1012, CSA-C22.2 No.107.1, EN61347-1, EN61347-2-13			
	WITHSTAND VOLTAGE	I/P – O/P: 3.75kVAC, I/P-FG: 2KVAC			
	ISOLTATION RESISTANCE	I/P – O/P: 100M Ohms / 500VDC /25℃ / 70% RH			
	EMC EMISSION	Compliance to EN55015, EN61000-3-2 Class C (≥60% load); EN61000-3-3			
	EMC IMMUNITY	Compliance to EN61000-4-2,3,4,5,6,8,11; EN61547, EN55024, light industry level (surge 2kV), criteria A			
OTHERS	MTBF	340khrs min.	MIL-HDBK-217F (25℃)		
	DIMENSIION	117(121)*49*33MM(L*W*H)			
	PACKING	380±10g			

<b>NOTE</b>	<ol style="list-style-type: none"> <li>1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and 25°C of ambient temperature.</li> <li>2. Ripple &amp; noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uf &amp; 47uf parallel capacitor.</li> <li>3. Tolerance: includes set up tolerance, line regulation &amp; load regulation.</li> <li>4. Please refer to "DRIVING METHODS OF LED MODULE".</li> <li>5. Derating may be needed under low input voltages. Please check the static characteristics for details.</li> <li>6. Suitable for indoor use or outdoor use without direct sunlight exposure. Please avoid immerse in the water over 30 minutes.</li> <li>7. Length of set up time is measured at cold first start. Turning ON/OFF the power supply may lead to increase of the set up time.</li> <li>8. The power supply is considered as a component that will be operated in combination with final equipment. Since EMC performance will be affected by the complete installation, the final equipment manufactures must re-qualify EMC DIRECTIVE on the complete installation again.</li> <li>9. Direct connecting to LEDs is suggested, but is not suitable for using additional drivers.</li> <li>10. To fulfill requirements of the latest ERP regulation for lighting fixtures, this LED power supply can only be used behind switch without permanently connected to the mains.</li> </ol>
-------------	--

## Mechanical Specification



# Derating Curve

